SHOCKFORM



The Spiker® ES is a needle peening tool that was designed for difficult-to-reach geometries.

ADVANTAGES

- Avoid risks of F.O.D.
- Intensity range 8N-15N/4A-16A
- Process date saved to USB key
- User-friendly color interface
- Very smooth surface finish
- Reliable and repeatable
- · Easy to print report
- Deep compressive residual stresses
- Adaptable end caps for different geometries
- Peen flat surfaces, inner and outer radiuses
- Small head for hard to Reach Areas
- · Significant cost saving potential
- · Fast and effective repair peening

Single needle head





4 needles linear head with 3 differents end caps











THE SPIKER® ES





SPECIFICATIONS

•	Central unit dimensions	L22.0 x W14.0 x H9.0 in (L559 x W356 x H229 mm)
•	Weight	21 lbs (9.5 Kg) empty, 27 lbs (12.3 Kg) fully loaded
•	Protection	Weather proof impact resistant NK-7 Resin Exterior
•	Control signal	Closed loop pressure feedback
•	Repeatibility	+/- 1 PSI
•	Pressure monitoring	Continuous with alarm
•	Solver	Integrated saturation curve solver for Almen intensity
•	Needle usage tracking	Yes
•	Data recording	Through 2GB USB Flash
•	Calibration setup	Yes
•	Display	7 inch 800 x 480 color touchscreen display
•	Pressure input	60 - 129 PSI (4 - 9 bar)
•	Handpiece cord length	25 Ft (7.7 m)
•	Electrical input	100 - 240V, 50/60 Hz, 3.0 A





4 NEEDLE HANDPIECE

1 NEEDLE HANDPIECE





Certification

CE