

NUPOWER II

PC2190 Series



NUPOWER II is a multi-functional drywash compound specially formulated to: clean, deoxidize, protect and preserve aircraft exterior paint. NUPOWER II removes all types of soil conditions including: surface dirt, carbon, lubricants, hydraulic fluids etc. while providing a smooth and glossy surface. NUPOWER II provides a surface barrier which seals the substrate against soil re-deposition and protects against UV deterioration.

APPLICATION

Apply NUPOWER II by hand, spray or mop head. Agitate area evenly while material is still wet. Allow to fully dry, approximately 5-10 minutes. Buff with a clean mop head or dry soft terry cloth to shine.

For heavily soiled surfaces, wipe or wet wash with **CitriCut** or **SS9-3** prior to using NUPOWER II.

For best results, please consult with UPI/Nuvite technical staff for further recommendations, and application techniques.

BENEFITS

- Effective soil removal
- Removes surface oxidation from paint and metal surfaces
- Preserves and protects against further oxidation, UV and atmospheric corrosion
- Safe to all aircraft components; conforms to airframe OEM standards and specifications

PHYSICAL CHARACTERISTICS

TEST	NUPOWER II
Appearance	Tan semi viscous liquid
pH	11.5 - 11.8
Specific gravity	0.940

AVAILABILITY

55 Gallon, 5 Gallon, 1 Gallon, 1 Quart, 1 Pint, 4 Oz., 1 Oz.